



RAPPRESENTANZE – COMMERCIO
TRASFORMAZIONI ARTICOLI INDUSTRIALI
Via F. Sanson ,47 - 25123 Brescia
Tel./Fax 030/361794
C.F. BROGTN29T25B157X P.IVA 00006080170

ABRASIVI RIGIDI E FLESSIBILI

NORTON

UTENSILI ELETTRICI ALTA FREQUENZA

UTENSILI PNEUMATICI

URYU

Smerigliatrice ad albero lungo

Smerigliatrice ad albero lungo **SUHNER, NPK, ATA** con pinza 6 – 8 – 10 mm

Lunghezza massima della smerigliatrice ad albero lungo 5000 mm

ATA STXX22LR-1 STXX16LR-1 STXX10LR-1 SGXX18LR-1

SGXX16LR-1 SGXX10LR-1 SHGX18LR-1 SHGX16LR-1 SHGX10LR-1

NPK NHG-65LKLW-75 NHG-65LDLW

SUHNER LSE18DH

Velocità Robustezza Alta qualità

La smerigliatrice ad albero lungo è adatta per i lavori di sbavatura e smerigliatura in luoghi difficilmente accessibili. Grazie al sistema delle **prolunghe**, la smerigliatrice ad albero lungo **Suhner LSE18DH** - 600 Watt può arrivare fino ad una lunghezza massima di **5 METRI !**

Disponibili differenti modelli delle smerigliatrici pneumatiche lunghe:

Smerigliatrice ad albero lungo ATA con potenza massima di 1100 Watt , lunghezza massima 1200 mm, pinza 6 – 8 – 10 mm oppure le mole abrasive a pera di diametro massimo 75 mm.

Smerigliatrice ad albero lungo NPK NHG-65LKLW-75 con potenza pari a 600 Watt, lunghezza massima 790 mm, pinza 6 – 8 mm; in versione NHG-65LDLW è in grado di montare mole abrasive diam. max 65 mm (e pinza 6 – 8 mm come optional).

Tutte le smerigliatrici pneumatiche lunghe hanno lo scarico posteriore dell'aria e l'impugnatura ergonomica.

Smerigliatrice ad albero lungo:

ATA STXX22LR-1, STXX16LR-1, STXX10LR-1, SGXX18LR-1, SGXX16LR-1, SGXX10LR-1, SHGX18LR-1, SHGX16LR-1, SHGX10LR-1

NPK NHG-65LKLW-75, NHG-65LDLW

SUHNER LSE18DH

ARTICOLI DI QUALITA' PER OGNI ESIGENZA **A PREZZI CONVENIENTI**



SUHNER LSE18

AVVIAMENTO	MODELLO	Ø PINZA	VELOCITA'	LUNGHEZZA MAX	PESO	POTENZA
		mm	rpm	mm	kg	watt
Leva di sicurezza	LSE18	6 mm	18.000	5000	1,8 *	600

* Senza prolunga



NPK NHG-65LDLW

AVVIAMENTO	MODELLO	Ø MOLA	VELOCITA'	LUNGHEZZA	PESO	POTENZA
Leva di sicurezza	NHG-65LDLW	mm 65x13x9,5	rpm 14.600	mm 538	kg 1,6	watt 440



NPK NHG-65LKLW75

AVVIAMENTO	MODELLO	Ø PINZA	VELOCITA'	LUNGHEZZA	PESO	POTENZA
Leva di sicurezza	NHG-65LKLW75	mm 6	rpm 18.000	mm 790	kg 2,2	watt 600

MODELLO STANDARD		ACCESSORI per smerigliatrice pneumatica NPK
NHG-65LDLW	Mola	Pinza 6 – 8 mm
NHG-65LKLW75	Pinza 6 mm	Pinza 8 mm



Long Reach Die Grinders

Modular extension system can be utilized for applications needing long reach access.

STXX Range 0.63 kW (0.85 hp)

Available in 22000, 16000 and 10000 rpm.

Type CA collet use up to 10mm (3/8") shanks.

22000 rpm
For 12-15mm (1/2"- 9/16") burs or 20mm (3/4") mounted points.

16000 rpm
For 30mm (1 3/16") flap wheels.

10000 rpm
For 50mm (2") flap wheels or drum sanders.

Heavy Duty modular spindle design.

Max metal removal with wheels up to 75mm (3") in diameter and 25mm (1") burs.

SHGX Range 1.10 kW (1.50 hp)

Available in 18000, 16000 and 10000 rpm.

Modular design allows for additional spindle assembly to be added.

18,000 rpm
For 50mm (2") mounted points or 25mm (1") burs.

16,000 & 10,000 rpm
For heavy metal removal with flap wheels.

SGXX Range 0.82 kW (1.10 hp)

Available in 18000, 16000 and 10000 rpm.

Each spindle assembly independently coupled to the next with a flexible coupling for long bearing life.

Spindle diameter 32mm (1 1/4") on all machines.

Sample Order Code

To order SGXX16LR with overall length of 866 mm (34.1")
Order SGXX16LR-4.

Model	Speed	Power	Diameter	Weight with (-) Ext	dBA	Standard Collet	Collet Option See P26	Air Consumed	Outlet	Hose Inlet	Hose	
	rpm	kW Hp	mm Inch	Kgs lbs		mm Inch		m ³ /min cfm				
0.85 hp	STXX22LR-1	22000	0.63 0.85	45.0 1.77	2.15 4.73	70	6.00 1/4"	CA	0.85 30.00	Rear	1/4"	Included
	STXX16LR-1	16000	0.63 0.85	45.0 1.77	2.15 4.73	65	6.00 1/4"	CA	0.85 30.00	Rear	1/4"	Included
	STXX10LR-1	10000	0.63 0.85	45.0 1.77	2.15 4.73	64	6.00 1/4"	CA	0.85 30.00	Rear	1/4"	Included
1.10 hp	SGXX18LR-1	18000	0.82 1.10	45.0 1.77	2.45 5.39	70	6.00 1/4"	CA	0.90 31.80	Rear	1/4"	Included
	SGXX16LR-1	16000	0.82 1.10	45.0 1.77	2.45 5.39	69	6.00 1/4"	CA	0.90 31.80	Rear	1/4"	Included
	SGXX10LR-1	10000	0.82 1.10	45.0 1.77	2.45 5.39	68	6.00 1/4"	CA	0.90 31.80	Rear	1/4"	Included
1.50 hp	SHGX18LR-1	18000	1.12 1.50	43.0 1.70	3.00 6.60	70	6.00 1/4"	CA	1.13 40.00	Rear	1/2"	Included
	SHGX16LR-1	16000	1.12 1.50	43.0 1.70	3.00 6.60	69	6.00 1/4"	CA	1.13 40.00	Rear	1/2"	Included
	SHGX10LR-1	10000	1.12 1.50	43.0 1.70	3.00 6.60	68	6.00 1/4"	CA	1.13 40.00	Rear	1/2"	Included

Overall tool length

Range	Option 1 (-1)	Option 2 (-2)	Option 3 (-3)	Option 4 (-4)	Option 5 (-5)	Option 6 (-6)	Option 7 (-7)
STXX	455 17.90	592 23.30	729 28.70	866 34.10	1003 39.50	1140 44.90	1277 50.25
SGXX	455 17.90	592 23.30	729 28.70	866 34.10	1003 39.50	1140 44.90	1277 50.25
SHGX	515 20.27	652 25.67	789 31.10	926 36.45	1063 41.85	1200 47.24	1337 52.63

Extra weight per extension

Kgs lbs

0.58 1.27



Long Reach Cone Wheel or Plug Stone Grinders

Lengths are available up to 1.20m (4ft).

STXX Range 0.63 kW (0.85 hp)

Available in 22000, 16000 and 10000 rpm.

0.63 kW (0.85 hp) for light grinding with plug stones up to 50mm (2") diameter

Available with thread
5/8-11
3/8-24
M10 x1.5

Heavy Duty modular spindle design.

STXX22LR-2-3/8"

SHGX18LR-3-5/8"

1.1 kW (1.50 hp) low noise - high power for maximum metal removal with plug stones up to 75mm (3") diameter.

0.63 kW (0.85 hp) Motor

Rear Exhaust.

SHGX Range 1.1 kW (1.50 hp)

1.1 kW (1.5 hp) Motor

SGXX 18 LR-1-M10

Available with thread
5/8-11
3/8-24
M10 x1.5

Heavy Duty modular spindle design.

0.82 kW (1.10 hp) for heavy grinding with stones up to 50mm (2") diameter.

SGXX Range 0.82 kW (1.10 hp)

0.82 kW (1.1 hp) Motor

Low Noise.

Rear exhaust.

Sample Order Code.
To order SHGX18LR with overall length 789mm (31.1") and 5/8 - 11 thread:
Order **SHGX18LR-3-5/8.**

Model	Speed	Power	Diameter	Weight with (-1) Ext	dBA	Air Consumed	Outlet	Hose Inlet	Hoses
	rpm	kW Hp	mm Inch	Kgs lbs		m ³ /min cfm			
0.85 hp STXX22LR-O-T	22000	0.63 0.85	45.0 1.77	2.15 4.73	70	0.85 30.00	Rear	1/4"	Included
	16000	0.63 0.85	45.0 1.77	2.15 4.73	65	0.85 30.00	Rear	1/4"	Included
	10000	0.63 0.85)	45.0 1.77	2.15 4.73	64	0.85 30.00	Rear	1/4"	Included
1.10 hp SGXX18LR-O-T	18000	0.82 1.10	45.0 1.77	2.45 5.39	70	0.90 31.80	Rear	1/4"	Included
	16000	0.82 1.10	45.0 1.77	2.45 5.39	69	0.90 31.80	Rear	1/4"	Included
	10000	0.82 1.10	45.0 1.77	2.45 5.39	68	0.90 31.80	Rear	1/4"	Included
1.50 hp SHGX18LR-O-T	18000	1.12 1.50	43.0 1.70	3.00 6.60	70	1.13 40.00	Rear	1/2"	Included
	16000	1.12 1.50	43.0 1.70	3.00 6.60	69	1.13 40.00	Rear	1/2"	Included
	10000	1.12 1.50	43.0 1.70	3.00 6.60	68	1.13 40.00	Rear	1/2"	Included

Overall tool length

Range	Option 1 (-1)	Option 2 (-2)	Option 3 (-3)	Option 4 (-4)	Option 5 (-5)	Option 6 (-6)	Option 7 (-7)
STXX	455 17.90	592 23.30	729 28.70	866 34.10	1003 39.50	1140 44.90	1277 50.25
SGXX	455 17.90	592 23.30	729 28.70	866 34.10	1003 39.50	1140 44.90	1277 50.25
SHGX	515 20.27	652 25.67	789 31.10	926 36.45	1063 41.85	1200 47.24	1337 52.63

Extra weight per extension

Kgs lbs

0.58 1.27